

HEMP252G SERIES:



200~250 Watt Single Output Models

- 7.46 x 3.74 x 1.89" Desktop Package

Features:

- Universal AC Input Range (90-264 VAC)
- Active Power Factor Correction (0.96 ~ 0.99 PF Typical)
- No-Load Power Consumption < 0.5W
- High Efficiency Operation up to 94%
- Compliant to Level V Efficiency Standards
- Medical & ITE Safety Approvals
- Class B Emissions
- 2 Year Warranty

INPUT:

Input Voltage	90~264 VAC (Universal AC Input)
Input Frequency	47-63Hz
Inrush Current	15.8Arms @ 230 VAC Cold Start
Input Current	1.95/1.0A @ 115 / 230 VAC
Input Protection	Dual Fuse
Hold-Up Time	20ms Minimum
Leakage Current	<300 μ A @ 240 VAC Maximum
Power Factor	EN61000-3-2 (0.96-0.99 PF Typical)

GENERAL:

Efficiency	88-94% minimum
Operating Temperature	0-40°C, derate linearly to 50% load at 50°C
Storage Temperature	-20°C to +85°C
Over-Temp Protection	Auto-Recovery
Cooling	Convection
Operating Humidity	5-90% RH, Non-Condensing
Vibration	5 ~ 50 Hz, acceleration 7.35 m/s*s on X,Y and Z Axis
MTBF	>100k Hrs (according to MIL-HBK-217F) at 30°C

OUTPUT:

Adjustment Range	Fixed at Factory (custom setpoints available)
Minimum Load	none required
Regulation	\pm 0.1% Line / \pm 3% Load max
Ripple & Noise	\pm 1% pk-pk @ 20MHz
Overload Protection	110-150% of max power (Foldback)
Over Voltage	Latching before 130% of nominal
Short Circuit Protection	Trip without damage & auto-recovery
Transient Response	recovers <1ms following a 50% load change
Switching Frequency	85-100KHz (Fixed)

APPROVALS:

Emissions	EN55022 "B", FCC Part 15 Subject J Class B
Safety Approvals	UL/cUL 60950-1 Listed UL/cUL 60601-1 Registered CE Mark (LVD)



HEMP252G SERIES:

Output Specifications:

Model:	Vout	Iout
HEMP252G-S120167-7	12V	16.7A
HEMP252G-S240104-7	24V	10.4A
HEMP252G-S480052-7	48V	5.2A

- Power Supply can be set to any voltage ranging between 12~48 VDC and maintain all safety approvals, consult APS for details
- Standard Cable Length is 6 feet.
- Additional suffix to designate output connector is required, see connector options at <http://www.advpower.com/images/prod/pdfs/connectors.pdf>

Mechanical Dimensions:

